



No Limits on Performance!



www.microtouchinc.com



3 Cylinder

Red Wire --

12 volt (Red) on Battery

Black Wire --

Ground (Black) on Battery


Yellow Wire --

Plug Wire Pick-up



Gray / Black- Red --

Wrap 3 - 4 times around each plug wire!



To Solenoid (Polarity does NOT matter)





On @ 2,000 RPM
 Buzz 1 5/8 5,900 RPM
 Buzz 2 4/8 6,100 RPM
 Buzz 3 3/8 6,300 RPM
 Buzz 4 2/8 6,500 RPM
 Off @ 6,700 RPM


On @ 2,000 RPM
 Buzz 1 5/8 6,100 RPM
 Buzz 2 4/8 6,300 RPM
 Buzz 3 3/8 6,500 RPM
 Buzz 4 2/8 6,700 RPM
 Off @ 6,900 RPM

On @ 2,000 RPM
 Buzz 1 5/8 6,000 RPM
 Buzz 2 4/8 6,200 RPM
 Buzz 3 3/8 6,400 RPM
 Buzz 4 2/8 6,600 RPM
 Off @ 6,800 RPM

On @ 2,000 RPM
 Buzz 1 5/8 6,200 RPM
 Buzz 2 4/8 6,400 RPM
 Buzz 3 3/8 6,600 RPM
 Buzz 4 2/8 6,800 RPM
 Off @ 7,000 RPM



Legend	
	= Jumper ON
	= Jumper OFF

NOTE: Keep controller mounted a few inches away from ignition coils or plug wires. Also keep grease on the fuse and the adjusting jumpers at all times to eliminate corrosion!